

Glossary H

[Return to main Glossary index](#)

Hall effect

This a transistor type that is effected by a magnetic field placed in close proximity
See MERG TBs A7/2/ 3/ 4 merg members only

Handset

Is a means of control in your hand.



Header plug or socket

Are plug & sockets primarily for use on PCB boards to make connections to and from the board



Heat sink

Waste heat is produced in transistors due to the current flowing through them. Heat sinks are needed for power transistors because they pass large currents. If you find that a transistor is becoming too hot to touch it certainly needs a heat sink! The heat sink helps to dissipate (remove) the heat by transferring it to the surrounding air.



<http://www.kpsec.freeuk.com/components/heatsink.htm>

Hector

This is a track detector using an optical system to detect the location of train Merg kit for members

High

This what we call greater than the base voltage or ground e.g. so high is 5v ~ 4.4volts above 0

HYPOTRAC

This a high voltage track detector system for 2 rail Model railway track , see TB T9/2 merg members only

Hysteresis loop

Hysteresis is wellknown in ferromagnetic materials. When an external magnetic field is applied to a ferromagnet, the ferromagnet absorbs some of the external field. Even when the external field is removed, the magnet will retain some field: it has become magnetized.

W [Hysteresis](#)

The term is also used to refer to one of the display modules often to be seen on the [MERG exhibition stand](#). This is because the track layout on the module resembles the graph of a [hysteresis loop](#).

From:
https://www.merg.org.uk/merg_wiki/ - **Knowledgebase**

Permanent link:
https://www.merg.org.uk/merg_wiki/doku.php?id=glossary:glossary_h&rev=1415712585

Last update: **2016/09/27 13:08**

