

Glossary L

[Return to main Glossary index](#)


Latching

Latching can apply to both mechanical devices and electronic circuits. An example of mechanical latching would be a push on / push off switch, [see here](#). See also description of a [latching relay](#). (e.g. [relay](#))

An example of an electronic latch would be [a flip-flop](#) or bistable circuit.

A standard relay may be made self latching by supplying a current path for the coil through one of its normally open contact sets.

LCC

[Layout Command Control](#) (LCC) is a system for controlling all the functions on your layout that don't  have to do with how fast the locomotive is moving – things like signals, or sounds, or passenger car lighting. LCC is NMRANet, just under a different name. LCC is designed as a separate, generic control bus which is positioned to take the load off your throttle bus. It is a bi-directional data bus that can send and receive data. Since it is an NMRA Standard, you are not confined to one manufacturer's products. Any manufacturer can make LCC compatible devices.

Lead free


This is a change in the content of solder. Lead free solder is generally recommended due to Health and Safety considerations, but 60:40 tin:lead is preferred for electronic kits and is still available from suppliers such as Rapid Electronics. It is important to note that lead and lead free solders require different soldering iron temperatures. DCC or dcc

LED

A Light Emitting Diode (LED) is a type of diode that emits light when an electric current is passed through it. LEDs can be manufactured to cover the visible spectrum as well as the IR and UV spectrums. LEDs come in many colors, sizes and styles, and some include multiple diodes internally allowing more than one color to be produced. LEDs are low voltage devices that usually require a resistor to limit the current through the device. Different LEDs will need different resistor values, even if they look similar.

Most LEDs, when manufactured, provide a way to tell the polarity. The longer leg is the anode or positive end. The shorter leg is usually the cathode or negative end (same as the banded end of a regular diode). Many larger LEDs may also have a flat part molded into the round base to indicate the cathode lead. If you cannot tell which leg is the positive you may try using a 680 ohm current limiting

resistor (or 1000 ohm with 12V) in series with the LED and a 5V power source to see which way lights the LED.



https://www.merg.org.uk/merg_resources/led.php
<http://electronicsclub.info/leds.htm>

LENZ

A German [DCC](#) system and decoder manufacturer.

LiFo

Last in First out, data buffer where the most recent entry is the first to be retrieved. Commonly referred to in programming as a 'Stack' it is used to save the return address (Program Counter) and other data that must be restored when a Sub Routine terminates.

Lighting decoder

A [DCC](#) decoder made especially for lights for a loco or carriages.

Logic

In a model railway it is a way to do step by step sequence to make the train do what you require. From an electronic component perspective, logic generally refers to IC logic gates that perform logical functions, such as AND, OR or Invert, to binary signals. A logic device may perform one function like ANDing two signals, or may be very complicated like a frequency divider IC.

<http://electronicsclub.info/74series.htm>

From:

https://www.merg.org.uk/merg_wiki/ - **Knowledgebase**

Permanent link:

https://www.merg.org.uk/merg_wiki/doku.php?id=glossary:glossary_l&rev=1628412677

Last update: **2021/08/08 08:51**

